

HX Production Group Limited

HK Address: Unit 11D, Tak Wing Ind Bldg, 3 Tsun Wen Rd, Hong Kong CN Address: 14 Qunhua Road, West Circle Road, Jiangmen, GD, China Tel: (86) 188 252 16380/ (852) 3525 1553 ; Fax: (852) 3525 1559

www.hxproductiongroup.com sales@hxproductiongroup.com

Material Data Sheet

PC Film/Sheet Product

HCGG-AG Hardcoat Anti-glare PC Sheet

DESCRIPTION

HCGG-AG PC Film/Sheet, produced in China, has excellent anti-glare surface with anti-scratches function. It becomes an increasing popularity using for display panel requiring non glare appearance. It's widely found in display panel of GPS navigation, POS touch panel, membrane switches for washing machine, oven, microwave, petrol station panel, etc. Available haze value from 3-80%

TYPICAL PROPERTY VALUE

Property	Standard Test	Unit	Results
PHYSICAL			
Color/Density	Transparent Clear	± 5 %	
Refraction Rate	JIS- D7105	%	1.49
Light Transmittion	ASTM - D 1003-61	% (min)	88.5
Haze	ASTM - D 1003-61	AG40 (HP12)	~ 40-45%
Haze	ASTM - D 1003-61	AG25 (HP40)	~ 23-25%
Haze	ASTM - D 1003-61	AG5 (HP60)	~ 5-7%
MECHANICAL			
Tensile Strength at Break	ASTM -D 638/882	kg/cm ²	480
Tensile Elongation at Break	ASTM -D 638/882	%	65.00
Izoo Test	ASTM -D 256-54T	kg.cm/cm	85
Pencil Hardness		JIS-D5400	HB
THERMAL			
Std. Temperature Resistance	ASTM - D 1525-76	°C	120
Heat Distortion Temperature	ASTM-D 1637	°C	140
Flammbility (if using UL resin)	UL94		V2
Melting Temperature	DSC Scanning	°C	255

Disclaimer

The information & value are intended for reference only. It does not guarantee the same data result, data safety and application suitability as described, nor is not considered a warranty or quality specification. Customer should carry its own test to determine your own particular use. The information relates only to the specific material designated and may not be vaild for such material used in combination with any other materials or in any process.